

Data sheet

THERMAL PRINTING

Print data:

- Please create the artwork in **Illustrator** (or in some cases in Photoshop), please make sure to create open and editable data (please ask us for the corresponding elevation drawings).
- The Microsoft programmes (Power Point, Word, Excel) do not produce reproducible data and are not suitable for printing.

Colours:

- **Please define colours in CMYK** and not in RGB mode. RGB data is converted to CMYK before printing, which may result in colour changes. Colour specifications such as Pantone, HKS, RAL as well as special colours (gold, silver, Pantone Reflex Blue etc.) are represented in the CMYK colour space and cannot be achieved exactly.
- Gold and silver can be represented with specially coloured thermal transfer foils.
- **Always create black fonts, lines and areas with 80c 60m 60y 100k.**
- Certain colour deviations may occur in reprints.

Document structure:

- **Please create the logos as vector graphics** (in individual cases, pixel data is possible after consultation).
- Please create large format prints only as vector graphics.
- Create data in scale 1:10 (min. 1500 ppi resolution) or 1:1 (min. 150 ppi resolution).
- Link images only and attach as a file (please do not embed images in the document).
- **Convert text to character paths (curves/paths) or include all fonts used.**
- You can obtain the respective elevation drawings in 1 :10 scale and create your design directly in this template, which can be opened in Illustrator. You will also find all our fabric colours in the colour fields. (The grey area only serves as a placeholder)
- Please send us larger amounts of data using a transfer provider, e.g. WeTransfer or our own Pro-Tent Transfer Tool
<https://pro-tent.com/files>
We will gladly provide you with the password upon request.

Another important piece of information about the sizes of the thermofoil: Please note that on the 36.5 cm high panel, the maximum logo height is 25 cm and with a panel height of 45 cm (4m tents) a maximum logo height of 33.5 cm is to be maintained. For the sloping roof and side wall, a logo size of 120 cm x 90 cm must not be exceeded.

The texts must not be less than 2 cm high and the lines must be at least 2 mm thick in order to guarantee adhesion of the film.

Other:

- We assume no liability for the accuracy of the content of data supplied.
- We do not provide any warranty for the product in case of faulty data.
- Data carriers, proofs or material samples are neither archived nor returned to the customer.
- Printed matter is exempt from any complaint unless a colour control printout has been provided.
- Our general terms and conditions apply. (www.pro-tent.ch/agb/)